



MAIN BIOS SETTINGS

Issue: Version 1.0 –
Cr   le 17/12/01 13:12

MTPC BOARD Version 1.00

L:\Product JPEG\LSM 2001\Install New
Chassis\Bios Settings\juky_biossettings.doc

Page 1 sur 1

ROM PCI/ISA BIOS (2A6LGI99)
STANDARD CMOS SETUP
AWARD SOFTWARE, INC.

Date (mm:dd:yy) : Fri, Nov 30 2001
Time (hh:mm:ss) : 18 : 3 : 0

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: Auto	0M	0	0	0	0	0	LBA
Primary Slave	: None	0M	0	0	0	0	0	----
Secondary Master	: None	0M	0	0	0	0	0	----
Secondary Slave	: None	0M	0	0	0	0	0	----

Drive A : 1.44M, 3.5 in.
Drive B : None

LCD&CRT : Both
Halt On : All, But Keyboard

Base Memory: 640K
Extended Memory: 7168K
Other Memory: 384K

Total Memory: **8192K**

ESC : Quit : Select Item PU/PD/+/- : Modify
F1 : Help (Shift)F2 : Change Color

ROM PCI/ISA BIOS (2A6LGI99)
INTEGRATED PERIPHERALS
AWARD SOFTWARE, INC.

OnChip IDE Channel0 : Enabled
OnChip IDE Channel1 : Enabled
IDE Prefetch Mode : Enabled
Primary Master PIO: Auto
Primary Slave PIO: Auto
Secondary Master PIO: Auto
Secondary Slave PIO: Auto
Primary Master UDMA: Auto
Primary Slave UDMA: Auto
Secondary Master UDMA: Auto
Secondary Slave UDMA: Auto
Init Display First : PCI Slot

KBC input clock : 8 MHz
Onboard FDC Controller: **Enabled**
Onboard Serial Port 1 : **3F8/IRQ4**
Onboard Serial Port 2 : **2F8/IRQ3**
UART Mode Select : **Normal**

Onboard Parallel Port : Disabled

ESC : Quit : Select Item
F1 : Help PU/PD/+/- : Modify
F5 : Old Values (Shift)F2 : Color
F6 : Load BIOS Defaults
F7 : Load Setup Defaults



MAIN BIOS SETTINGS

Issue: Version 1.0 –
Cr    le 17/12/01 13:12

MTPC BOARD Version 1.00

L:\Product JPEG\LSM 2001\Install New
Chassis\Bios Settings\juky_biossettings.doc

Page 2 sur 2

ROM PCI/ISA BIOS (2A6LGI99) POWER MANAGEMENT SETUP AWARD SOFTWARE, INC.

Power Management : User Define	Primary Intr : OFF
PM Control by APM : Yes	
Video Off After : Suspend	
Video Off Method : V/H SYNC+Blank	
MODEM Use IRQ : 3	
HDD Power Down : Disable	
Doze Mode : Disable	
Suspend Mode : Disable	
** PM Events **	
VGA : OFF	
LPT & COM : LPT/COM	
HDD & FDD : ON	
DMA/master : OFF	
ESC : Quit : Select Item	
F1 : Help PU/PD/+/- : Modify	
F5 : Old Values (Shift)F2 : Color	
F6 : Load BIOS Defaults	
F7 : Load Setup Defaults	

ROM PCI/ISA BIOS (2A6LGI99) PNP/PCI CONFIGURATION AWARD SOFTWARE, INC.

PNP OS Installed : No	
Resources Controlled By : Manual	
Reset Configuration Data : Disabled	
IRQ-3 assigned to : PCI/ISA PnP	
IRQ-4 assigned to : PCI/ISA PnP	
IRQ-5 assigned to : Legacy ISA	
IRQ-7 assigned to : Legacy ISA	
IRQ-9 assigned to : Legacy ISA	
IRQ-10 assigned to : Legacy ISA	
IRQ-11 assigned to : Legacy ISA	
IRQ-12 assigned to : PCI/ISA PnP	
IRQ-14 assigned to : PCI/ISA PnP	
IRQ-15 assigned to : PCI/ISA PnP	
DMA-0 assigned to : PCI/ISA PnP	
DMA-1 assigned to : PCI/ISA PnP	
DMA-3 assigned to : PCI/ISA PnP	
DMA-5 assigned to : PCI/ISA PnP	
DMA-6 assigned to : PCI/ISA PnP	
DMA-7 assigned to : PCI/ISA PnP	
ESC : Quit : Select Item	
F1 : Help PU/PD/+/- : Modify	
F5 : Old Values (Shift)F2 : Color	
F6 : Load BIOS Defaults	
F7 : Load Setup Defaults	

Bank 0/1 DRAM Timing : SDRAM 8/10ns SDRAM Cycle Length : 3 Memory Hole : Disabled System BIOS Cacheable : Disabled Video RAM Cacheable : Disabled OnChip USB : Disabled	
	ESC : Quit : Select Item F1 : Help PU/PD/+/- : Modify F5 : Old Values (Shift)F2 : Color F6 : Load BIOS Defaults F7 : Load Setup Defaults