

XHUB-VIA 1U Hardware Manual

2019-06-12 / TR-XHUB-VIA

Commercial Reference

▣ XHUB-VIA-F2R : XHub-Via F2R



front view

Mechanical

Size:	43.8mm (H) x 200mm (W) x 508mm (D) 1.72" (H) x 7.87" (W) x 20" (D)
Mounting:	19" Rack mount
Weight:	4.500kg
Speed:	10/25/40/50/100GbE per port
Connector cage:	18 ports of 10/25GbE and 4 splittable ports of 40/100GbE

Environmental

Temperature:	Operational: 0° to 40°C Non-Operational: -40° to 70°C
Humidity:	Operational: 10% - 85% non-condensing Non-Operational: 10% - 90% non-condensing
Altitude:	3050m
Noise level:	73.7 dB(A)

Regulatory

Safety/ EMC:	CB, cTUVus, CE, CU, S_Mark, CE, FCC, VCCI, ICES, RCM, BSMI, KCC, CCC
RoHS:	RoHS compliant

Power

Input Voltage:	100-127VAC 50/60Hz 4.5A; 200-240 50/60Hz 2.9A
Global Power Consumption:	Typical power with passive cables (ATIS): 57W Max power with optical cables (assuming 3.5W per each QSFP28 port): 250W