

TABLE OF CONTENTS

1. OVERVIEW.....	1
2. CARD EDGE CONTROLS.....	2
2.1. DETERMINING CURRENT IP ADDRESS SETTINGS.....	2
2.2. RESTORING FACTORY DEFAULTS.....	2
2.3. CARD EDGE LEDS.....	2
3. CONFIGURATION.....	3
3.1. CONFIGURATION STEPS.....	3
3.2. DEBUG/MONITOR PORT CONNECTION	3
3.3. MAIN MENU	5
3.4. NETWORK CONFIGURATION.....	5
3.5. SERIAL PORT SETUP	5
3.5.1. Parameters	5
3.5.2. Back Plate.....	6
3.5.3. RS-232 Wiring	7
3.5.4. RS-422 Wiring	8
3.6. SNMP SETUP.....	9
3.7. RCL PROTOCOL SETTINGS.....	9
3.7.1. RCL Client Type	9
3.7.1.1. Enabling Serial RCL Client.....	9
3.7.1.2. Enabling Ethernet RCL Client.....	9
3.7.2. Level Bitmap	10
3.7.2.1. Serial RCL Client	10
3.7.2.2. Ethernet RCL Client.....	10
3.7.3. Areas	10
3.7.3.1. Serial RCL Client	11
3.7.3.2. Ethernet RCL Client.....	11
3.7.4. Filtering Non-Configured Sources & Destinations	11
3.7.4.1. Serial RCL Client	13
3.7.4.2. Ethernet RCL Client.....	13
3.7.5. Transmit Notification Response.....	13
3.8. UNDER MONITOR DISPLAY SETUP	13
4. TROUBLESHOOTING TIPS.....	15
4.1. VLPRO NOTES	15

4.2.	CHECKING SERIAL CONTROLLER COMMUNICATION	15
4.3.	CHECKING UMD PEER COMMUNICATION.....	16
4.4.	CHECKING ETHERNET CONTROLLER COMMUNICATION	17
4.5.	POLLING.....	17
5.	PERFORMING A FIRMWARE UPGRADE.....	18
5.1.	FTP.....	18
5.2.	SERIAL.....	18

Figures

Figure 1-1: Typical 7700PTX-RCL Serial Setup.....	1
Figure 1-2: Typical 7700PTX-RCL Ethernet Setup	1
Figure 2-1: PTX Card Edge	2
Figure 3-1: Upgrade Jumper	3
Figure 3-2: 'Connect To' Window	4
Figure 3-3: COM1 Properties	4
Figure 3-4: 7700PTX Back Plate	6
Figure 3-5: RS-232 Pins	7
Figure 3-6: RS-422 Pins	8
Figure 3-7: UMD Example	14
Figure 4-1: Communication States	16
Figure 4-2: Ethernet Communication State	17

Tables

Table 3-1: 7700PTX-RCL Main Menu	5
Table 3-2: Serial Port Parameters	5
Table 3-3: RS-232 Wiring	7
Table 3-4: RS-422 Wiring	8
Table 3-5: SNMP Parameters	9
Table 3-6: Supported Number of Controller Sources/Destinations	10

REVISION HISTORY

<u>REVISION</u>	<u>DESCRIPTION</u>	<u>DATE</u>
1.0	Preliminary	Sept 05
1.1	Standardized Format	Mar 07
1.2	Updated card edge drawing	Nov 07
1.3	Fixed typos	Feb 08

Information contained in this manual is believed to be accurate and reliable. However, Evertz assumes no responsibility for the use thereof nor for the rights of third parties, which may be effected in any way by the use thereof. Any representations in this document concerning performance of Evertz products are for informational use only and are not warranties of future performance, either express or implied. The only warranty offered by Evertz in relation to this product is the Evertz standard limited warranty, stated in the sales contract or order confirmation form.

Although every attempt has been made to accurately describe the features, installation and operation of this product in this manual, no warranty is granted nor liability assumed in relation to any errors or omissions unless specifically undertaken in the Evertz sales contract or order confirmation. Information contained in this manual is periodically updated and changes will be incorporated into subsequent editions. If you encounter an error, please notify Evertz Customer Service department. Evertz reserves the right, without notice or liability, to make changes in equipment design or specifications.

This page left intentionally blank

1. OVERVIEW

The 7700PTX-RCL is a network-controlled protocol translator designed to translate SNMP application commands into GVG Router Control Language (RCL) protocol packets. Translated packets are transmitted to one of up to four Encore controllers.

Figure 1-1 shows how the 7700PTX-RCL is typically set up for serial communication.




Figure 1-1: Typical 7700PTX-RCL Serial Setup

Figure 1-2 shows how the 7700PTX-RCL is typically set up for Ethernet communication.




Figure 1-2: Typical 7700PTX-RCL Ethernet Setup

2. CARD EDGE CONTROLS

2.1. DETERMINING CURRENT IP ADDRESS SETTINGS

To read the current IP address during normal operation, press the toggle switch DOWN. The IP address can be read on the four-character alphanumeric display.

2.2. RESTORING FACTORY DEFAULTS

To restore all settings to factory defaults, apply power to the card while holding the toggle switch UP until the green LED illuminates.

2.3. CARD EDGE LEDS

LED 22 is illuminated when Ethernet activity is detected.

All other card edge LEDs are for factory use only.




Figure 2-1: PTX Card Edge

3. CONFIGURATION

3.1. CONFIGURATION STEPS

Perform the following steps to configure the 7700PTX-RCL:

1. Connect a PC running a console application to the PTX debug/monitor port via the adapter cable.
2. Configure the 7700PTX-RCL's network parameters.
3. Decide if the 7700PTX-RCL will communicate with the Encore controller via serial or Ethernet.
4. For serial communication, configure the parameters of each serial port of the 7700PTX-RCL to match those of the SIO port(s) of the Encore controller. Configure the 7700PTX-RCL to act as a serial RCL client.
5. For Ethernet communication, configure on the 7700PTX-RCL the IP address of the Encore controller, and configure the 7700PTX-RCL to act as an Ethernet RCL client.
6. If required, configure the parameters related to the Router Control Language protocol.
7. If required, specify what area(s) the 7700PTX-RCL are to monitor/control.
8. Configure UMD peers if required.
9. Power off the 7700PTX-RCL.
10. If the 7700PTX-RCL is to act as a serial RCL client, physically wire its serial port(s) to the SIO port(s) of the Encore controller.
11. Power on the 7700PTX-RCL.



The 7700PTX-RCL is normally connected to the master Quartz router.

3.2. DEBUG/MONITOR PORT CONNECTION

The 7700PTX-RCL is configured via the debug/monitor port, the header of which is labelled J1. A special Evertz adapter cable allows this port to connect to the COM port of a personal computer. The following steps describe this procedure.

1. Locate the small, keyed, four-pin end of the upgrade cable provided by Evertz.
2. Connect it to the four-pin interface (J1) near the front of the 7700PTX, directly above the card unlock latch.




Figure 3-1: Upgrade Jumper

3. Connect the other end of the upgrade cable to a straight-through serial cable. Connect the serial cable to the serial or COM port of the computer.
4. Initiate HyperTerminal on your computer by selecting:
"Start\Programs\Accessories\Communications\HyperTerminal".
5. Enter a name for your connection, for example: PTX.
6. Press the <Enter> key. A new "Connect To" window opens.



Figure 3-2: 'Connect To' Window

7. Select COM1 for the "Connect using" setting. If COM1 is in use, choose an alternate COM port.
8. Press the <Enter> key or select OK. This opens the "COM Properties" window.




Figure 3-3: COM1 Properties

9. Enter the information as listed in the screen above.
10. Press the <Enter> key or select OK. The "COM Properties" window closes, leaving the HyperTerminal window open.

11. Apply power if the 7700PTX-RCL does not have power. The boot sequence and Main Menu are displayed in the HyperTerminal window.
12. If the 7700PTX-RCL has power, press the <Enter> key to view the 7700PTX-RCL's menu system.
13. Various 7700PTX-RCL parameters are configurable via the 7700PTX-RCL's menu system, the root of which is called *Main Menu*.

3.3. MAIN MENU

Table 3-1 lists the entries available in the 7700PTX-RCL's *Main Menu*.

Entry	Item	Notes
1	Network Configuration	IP address, subnet mask, gateway, etc.
2	Serial Port Setup	Baud rate, number of data bits, etc. of serial ports which connect to Encore controller(s)
3	SNMP Setup	IP address of SNMP manager(s) to receive traps
4	RCL Protocol Setup	Settings specific to the Router Control Language protocol
5	Under Monitor Display Setup	IP address and TCP port of PPV to receive the description of the input associated with a particular output
6	Engineering/Debug	Used for troubleshooting

Table 3-1: 7700PTX-RCL Main Menu

3.4. NETWORK CONFIGURATION

1. From the *Main Menu* select *Network Configuration*.
2. If DHCP (Dynamic Host Configuration Protocol) is desired, then the *Use DHCP* field is set to *True*. Otherwise, the IP address, subnet mask, and gateway (if any) are set and the *Use DHCP* field set to *False*.
3. Once the network settings are configured, select *Save* and *Exit* before exiting *Network Configuration* to save the settings, otherwise select *Exit*.



The 7700PTX-RCL must be rebooted for any network setting changes to take effect.

3.5. SERIAL PORT SETUP

3.5.1. Parameters

The 7700PTX-RCL has four serial ports. The parameters associated with each serial port are listed in Table 3-2. Typically, the Quartz router is set to 38400 baud, 8 data bits, no parity, 1 stop bit.

Parameter	Special Notes
Baud Rate	
Data Bits	
Parity	
Stop Bits	
Standard	For serial port 4, only RS-232 is valid.

Table 3-2: Serial Port Parameters



The serial port settings of the 7700PTX-RCL must match those of the router(s). The 7700PTX-RCL must be rebooted for any serial parameter changes to take effect.

3.5.2. Back Plate




Figure 3-4: 7700PTX Back Plate

3.5.3. RS-232 Wiring

Figure 3-5 shows which pins of the back plate are used for RS-232 serial connections.




Figure 3-5: RS-232 Pins

Table 3-3 details how to connect the 7700PTX-RCL to the router for RS-232 operation.

7700PTX-RCL			Router	
Port	Pin Name	Pin	DB9 Male Pin	Pin Name
1	TXA	1	3	RX
	RXA	2	7	TX
	GND	6	6	GND
2	TXB	7	3	RX
	RXB	8	7	TX
	GND	12	6	GND
3	TXC	13	3	RX
	RXC	14	7	TX
	GND	22	6	GND
4	TXD	23	3	RX
	RXD	24	7	TX
	GND	26	6	GND

Table 3-3: RS-232 Wiring

3.5.4. RS-422 Wiring

Figure 3-6 shows which pins of the back plate are used for RS-422 serial connections.




Figure 3-6: RS-422 Pins

Table 3-4 details how to connect the 7700PTX-RCL to the router for RS-422 operation.

7700PTX-RCL			Router	
Port	Pin Name	Pin	Pin	Pin Name
1	TX-A	1	8	RX-
	TX+A	3	3	RX+
	RX-A	2	2	TX-
	RX+A	4	7	TX+
	GND	6	6	GND
2	TX-B	7	8	RX-
	TX+B	9	3	RX+
	RX-B	8	2	TX-
	RX+B	10	7	TX+
	GND	12	6	GND
3	TX-C	13	8	RX-
	TX+C	15	3	RX+
	RX-C	14	2	TX-
	RX+C	16	7	TX+
	GND	22	6	GND

Table 3-4: RS-422 Wiring



The 7700PTX-RCL's fourth serial port is not RS-422 capable.

3.6. SNMP SETUP

Table 3-5 lists the parameters associated with the SNMP setup.

Parameter	Notes
Read-only community	Community string used for SNMP gets. The default is <i>public</i> .
Read-write community	Community string used for SNMP gets or sets. The default is <i>private</i> .

Table 3-5: SNMP Parameters



These parameters must match those of the SNMP manager. Changes to these parameters do not require a reboot of the 7700PTX-RCL.

3.7. RCL PROTOCOL SETTINGS

3.7.1. RCL Client Type

The Encore controller is a RCL server. The 7700PTX-RCL is a RCL client. There are 2 types of RCL clients: serial and Ethernet. The 7700PTX-RCL supports both client types, but not simultaneously. The default setting is a serial RCL client.

3.7.1.1. Enabling Serial RCL Client

To enable the 7700PTX-RCL to act as a serial RCL client follow the steps below:

1. From *Main Menu* select *RCL Protocol Settings Setup*.
2. Select *Enable serial RCL client*.
3. The 7700PTX-RCL must be rebooted for the client type changes to take effect.

3.7.1.2. Enabling Ethernet RCL Client

To enable the 7700PTX-RCL to act as an Ethernet RCL client that communicates with the Encore controller over TCP, follow the steps below:

1. From *Main Menu* select *RCL Protocol Settings Setup*.
2. Select *Enable Ethernet RCL client*.
3. Select *RCL Ethernet Settings Setup*.
4. Select *RCL server IP address/TCP port setup*.
5. Select *Set Encore IP address*.
6. Enter the IP address of the Encore controller.
7. Select *Save and Exit*.
8. The 7700PTX-RCL must be rebooted for the client type changes to take effect.

3.7.2. Level Bitmap

When enabled, the 7700PTX-RCL includes a level bitmap with the appropriate commands it transmits to the Encore controller. The level bitmap is a 32-bit quantity in which each bit specifies the presence (bit = 1) or absence (bit = 0) of a particular level. If no level bitmap accompanies a command that supports it, then all levels are used.

By default the 7700PTX-RCL does not use a level bitmap. If a level bitmap is required it can be configured on a per-port basis:

3.7.2.1. Serial RCL Client

1. From *Main Menu*, select *RCL Protocol Settings Setup*.
2. Select *RCL Serial Settings Setup*.
3. Select *RCL Protocol Setup For Port 1* (if the Encore controller is connected to the 7700PTX-RCL second serial port then select *RCL Protocol Setup For Port 2*).
4. Select *Set level bitmap usage*.
5. Select *y* when prompted.
6. Use *Set individual level* and *Set all levels* to set/clear the appropriate levels in the bitmap.
7. Select *Save and Exit* to start using the level bitmap. No reboot of the 7700PTX-RCL is required.

3.7.2.2. Ethernet RCL Client

1. From *Main Menu* select *RCL Protocol Settings Setup*.
2. Select *RCL Ethernet Settings Setup*.
3. Select *RCL Protocol Setup For Port 1*.
4. Select *Set level bitmap usage*.
5. Select *y* when prompted.
6. Use *Set individual level* and *Set all levels* to set/clear the appropriate levels in the bitmap.
7. Select *Save and Exit* to start using the level bitmap. No reboot of the 7700PTX-RCL is required.



Unless there is a specific need for it, level bitmap usage should not be enabled.

3.7.3. Areas

The maximum number of controller sources and destinations supported on a per-port basis is shown in Table 3-6.

Port	Maximum Number of Sources	Maximum Number of Destinations
Serial 1	4096	2048
Serial 2	4096	2048
Serial 3	4096	2048
Serial 4	4096	2048
Ethernet	4096	2048

Table 3-6: Supported Number of Controller Sources/Destinations

Should the total number of sources and/or destinations configured on the controller exceed these limits, or if you are interested in controller 1 or more specific areas, configure area names on the 7700PTX-RCL.

The Encore controller can partition the router system into smaller units called areas with each area having some user-assigned name. The 7700PTX-RCL can manage up to 16 different areas. The 7700PTX-RCL manages all areas (the default) when no area names are specified.

Configure Area names on the 7700PTX-RCL as follows:

3.7.3.1. Serial RCL Client

1. From *Main Menu* select *RCL Protocol Settings Setup*
2. Select *RCL Serial Settings Setup*
3. Select *RCL Protocol Setup For Port 1* (if the Encore controller is connected to the 7700PTX-RCL second serial port the *RCL Protocol Setup For Port 2* would be selected)
4. Use *Add/edit area name* and *Remove area name* to configure the areas of interest
5. If you do not wish the 7700PTX-RCL to report area names to VLPro or to propagate them to UMDs, select *Set area name reporting usage* and then select *y*
6. Select *Save And Exit* to start using the configured area names. No reboot of the 7700PTX-RCL is required

3.7.3.2. Ethernet RCL Client

1. From *Main Menu* select *RCL Protocol Settings Setup*
2. Select *RCL Ethernet Settings Setup*
3. Select *Protocol Setup For Port 1*.
4. Use *Add/Edit area name* and *Remove area name* to configure the areas of interest
5. If you do not wish the 7700PTX-RCL to report area names to VLPro or to propagate them to UMDs, select *Set area name reporting usage* and then select *y*
6. Select *Save And Exit* to start using the configured area names. No reboot of the 7700PTX-RCL is required



The use of area names is strongly recommended. If no areas are specified then the 7700PTX-RCL will assume *all* areas.

3.7.4. Filtering Non-Configured Sources & Destinations

Until a source is enabled within the Encore controller system it assumes the default name *NOSRC*. Until a destination is enabled it assumes the default name *NODST*. By default these are *not* filtered by the 7700PTX-RCL, preserving the actual router density. For example, suppose we have a 16-source and 16-destination router system where only 2 sources and 2 destinations are configured. By not filtering non-configured source and destination names the 7700PTX-RCL will report the correct router system size (16 x 16). If the 7700PTX-RCL were to filter, it would report a router system size of (2 x 2). Filtering non-configured names is desirable only when they fall at the end of a system. For instance, it is possible to have the following on an 8-source system:

Source Number	Name	7700PTX-RCL Assigned Number
1	Cam1	1
2	Cam2	2
3	Cam3	3
4	Cam4	4
5	NOSR C	
6	NOSR C	
7	NOSR C	
8	NOSR C	

Filtering the names for this scenario does not present non-configured sources to the user. Furthermore, since the configured names are contiguous, the source number assigned by the 7700PTX-RCL (and used by VLPro) will be valid.

Consider this scenario where the configured names are not contiguous and the non-configured source names are filtered:

Source Number	Name	7700PTX-RCL Assigned Number
1	Cam1	1
2	Cam2	2
3	NOSR C	
4	NOSR C	
5	NOSR C	
6	NOSR C	
7	Cam 3	3
8	Cam 4	4

Suppose source number 3 is enabled:

Source Number	Name	7700PTX-RCL Assigned Number
1	Cam1	1
2	Cam2	2
3	Bars	3
4	NOSR C	
5	NOSR C	
6	NOSR C	
7	Cam 3	4
8	Cam 4	5

As you can see, the numbers assigned by the 7700PTX-RCL to the last 2 configured sources have changed. If VLPro were to use any macros using assigned source numbers 3 and 4 these macros would now be invalid as assigned numbers 3 & 4, due to the Encore configuration change, correspond to Bars and *Cam3*, not *Cam3* and *Cam4*.

To change this setting follow the steps below:

3.7.4.1. Serial RCL Client

1. From *Main Menu* select *RCL Protocol Settings Setup*.
2. Select *RCL Serial Settings Setup*.
3. Select *RCL Protocol Setup For Port 1* (if the Encore controller is connected to the 7700PTX-RCL second serial port the *RCL Protocol Setup For Port 2* would be selected).
4. Select *Filter out non-configured sources & destinations*. Select the setting.
5. Select *Save And Exit*. No reboot of the 7700PTX-RCL is required.

3.7.4.2. Ethernet RCL Client

1. From *Main Menu* select *RCL Protocol Settings Setup*.
2. Select *RCL Ethernet Settings Setup*.
3. Select *RCL Protocol Setup For Port 1*.
4. Select *Filter out non-configured sources & destinations*. Select the setting.
5. Select *Save And Exit*. No reboot of the 7700PTX-RCL is required



Filter non-configured source and destinations only if Encore's configured sources and destinations are contiguous.

3.7.5. Transmit Notification Response

Leave this parameter set to the default *no* unless the Encore controller requires a L4 response to its unsolicited notification message.

3.8. UNDER MONITOR DISPLAY SETUP

The 7700PTX-RCL has the ability to transmit router source label information to the UMDs of up to 12 PPVs. As an example, suppose we have the setup of Figure 3-7




Figure 3-7: UMD Example

Where:

- A router has 3 inputs connected (labelled Input 1, Input 2, and Input 3) and 1 output (labelled Output 1)
- A 7700PTX-RCL monitors the router cross points
- An MVP contains a PPV with IP address 192.168.18.30
- The PPV is set to receive UMD data via the Image Video protocol over a TCP, with TCP port configured at 9800
- Protocol ID (PID) set to 1
- A PC running VistaLINK® Pro configures the 7700PTX-RCL so that the UMD PID associated with router Output 1 matches the PID of the UMD (for example, 1)

The *Under Monitor Display Setup* menu allows the configuration of the IP address and TCP port of the PPV to receive router source label information. In keeping with the above example, the 7700PTX-RCL would be configured to have a peer 1 IP address of 192.168.18.30 and a TCP port of 9800. When router input 1 is on output 1, the UMD of the display should display INPUT 1. If the cross point is switched to input 3, the UMD should display INPUT 3.



The 7700PTX-RCL must be rebooted for any UMD peer changes to take effect.

4. TROUBLESHOOTING TIPS

4.1. VLPRO NOTES

1. The 7700PTX-RCL must be able to communicate with any connected controllers in order for VLPro to operate properly.
2. The 7700PTX-RCL must be able to communicate with its configured UMD peers before UMD information can be transmitted.
3. VLPro must associate a UMD protocol ID with a router output in order for UMD information to be transmitted.

4.2. CHECKING SERIAL CONTROLLER COMMUNICATION

1. From the *Main Menu* select *Engineering/Debug*.
2. Select *Show task state*.
3. There are four entries, one for each serial port, listed under the heading *Router protocol PCB state*... If the state associated with the serial port is reported as *ready* then the 7700PTX-RCL is actively communicating with the controller on that port. If the state is consistently reported as *down* then the 7700PTX-RCL is unable to communicate with the controller in which case the serial port settings or wiring should be checked.
4. Figure 4-1 shows the 7700PTX-RCL is able to communicate with a controller connected to port 2.

```

dbg_1_115 - HyperTerminal
File Edit View Call Transfer Help

***
Port      Dst Address      Tcp Port      Status
****      *****
E1        192.168.18.40    9800          ready
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set
E1        0.0.0.0          0             no address set

router protocol task state: ready

router protocol PCB state...
1         down
2         ready
3         down
4         down

Connected 2:36:23  ANSI  115200 8-N-2  SCROLL  CAPS  NUM  Capture  Print echo
  
```


Figure 4-1: Communication States

4.3. CHECKING UMD PEER COMMUNICATION

1. From the *Main Menu* select *Engineering/Debug*.
2. Select *Show task state*.
3. There are up to 12 UMD peer entries listed under the heading *UMD peer status...* A status reported as *ready* indicates the 7700PTX-RCL is able to communicate with that UMD peer. A status consistently reported as something other than *ready* indicates the inability of the 7700PTX-RCL to communicate with that UMD peer. Ensure that the UMD peer has been rebooted after being configured to receive the Image Video over TCP.
4. Figure 4-1 shows the 7700PTX-RCL able to communicate with the UMD peer whose IP address is 192.168.18.40 who is listening on TCP port 9800.

4.4. CHECKING ETHERNET CONTROLLER COMMUNICATION

1. From the *Main Menu* select *Engineering/Debug*.
2. Select *Show task state*.
3. As per Figure 4-2, *router protocol PCB state 1* should appear as *ready*. This reports the 7700PTX-RCL's ability to exchange RCL protocol data with the controller. The *Router Ethernet state* should appear as *ready*. This reports the 7700PTX-RCL's ability to exchange TCP data with the controller. If this state is consistently reported as *down* then you should check the IP address of the server, the server's ability to receive TCP traffic over TCP port 12345, use a computer to ping both the 7700PTX-RCL and the controller.



```

dbg_1_115 - HyperTerminal
File Edit View Call Transfer Help

E1      0.0.0.0      0      no address set
E1      0.0.0.0      0      no address set
E1      0.0.0.0      0      no address set
E1      0.0.0.0      0      no address set
E1      0.0.0.0      0      no address set
E1      0.0.0.0      0      no address set
E1      0.0.0.0      0      no address set
E1      0.0.0.0      0      no address set

router protocol task state: ready

router protocol PCB state...
  1      ready
  2      no disp state routine
  3      no disp state routine
  4      no disp state routine

SNMP agent: ready

Server communication handler state: awaiting connection
currently listening on port: 9674

Router ethernet state: ready
connected to server: 192.168.18.40 port 9193

Connected 1:04:10  ANSI  115200 8-N-2  SCROLL  CAPS  NUM  Capture  Print echo
  
```

Figure 4-2: Ethernet Communication State

4.5. POLLING

If the Encore controller is configured to lose its subscriptions over time then the 7700PTX-RCL will need to be configured to have a poll duration. The duration specifies the amount of time, in seconds, between polling cycles. A polling cycle consists of a refresh of all pertinent notifications. By default, the 7700PTX-RCL is not configured to refresh these notifications – the assumption being the Encore controller will not expire them (which is typical).

The poll duration can be changed via the *Set Router Poll Status* entry of the *Engineering/Debug* menu. The time between polls can be set on a per-serial port basis. If 0 is selected as the time between polls, polling is disabled (the default).

Once set, the router poll status setting takes effect immediately; no reboot is necessary. It is saved to flash and recalled should the 7700PTX-RCL be powered off, then on.

5. PERFORMING A FIRMWARE UPGRADE

There are two ways to upgrade PTX firmware:

1. Using FTP to perform the upgrade via TCP/IP. (*recommended procedure*)
2. Using a terminal application such as *HyperTerminal* to perform the upgrade via a serial connection.

5.1. FTP

1. Open a command prompt window (in Windows: Start/Programs/Accessories/Command Prompt)
2. Enter the location of the firmware file. For example, type `cd c:\temp`.
3. Enter the command `ftp` followed by the PTX IP address.
For example, type `ftp -A 192.168.18.22`.
4. Enter the FTP command `put` followed by the firmware file name. For example, `put ptx.bin`.
5. When the transfer is complete enter the FTP command: `bye`.
6. Step 5 begins the process of saving the firmware to the non-volatile flash of the PTX. The save process is displayed as a percentage on the PTX LCD. Once the process is complete, the PTX LCD again displays the product name and firmware version.
7. Power off the PTX.
8. Power on the PTX.

5.2. SERIAL

1. Power off the PTX.
2. Connect an adapter cable to a PC running a console or terminal application, such as Windows *HyperTerminal*, to the PTX debug/monitor port.
3. Configure the port settings of the terminal program as follows:

Baud	115200
Parity	no
Data bits	8
Stop bits	2
Flow Control	None

4. Set the PTX run/upgrade jumper to the upgrade position.
5. Power on the PTX.
6. After a few moments, the prompt `PPCBOOT>` will appear. Enter the command `upload`.
7. Start the firmware upload on the terminal application (for instance, in *HyperTerminal* select Transfer/Send File...), use Xmodem as the transfer protocol, and select the firmware file. For example, `ptx.bin`.
8. Once the upload is complete the message `upload okay` is displayed.
9. Power off the PTX.
10. Set the PTX run/upgrade jumper to the run position.
11. Remove the serial adapter cable.
12. Power on the PTX.