



8761 Paired - Audio, Control and Instrumentation Cable



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

22 AWG stranded (7x30) tinned copper conductors, twisted pair, polyethylene insulation, overall 100% Beldfoil® shield, 22 AWG stranded tinned copper drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	22
Stranding	7x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PE - Polyethylene
Nom. Insulation Wall Thickness	.016 in.
Lay Length	1.5 in.
Twists/ft.	8

Pair Color Code Chart :

Number	Color
1	Black & Clear

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil® (Z-Fold®)
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	22
Outer Shield Drain Wire Stranding	Stranded
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------



8761 Paired - Audio, Control and Instrumentation Cable

Outer Jacket Nominal Wall Thickness	.025 in.
-------------------------------------	----------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.175 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +60°C
UL Temperature Rating	60°C (UL AWM Style 2092)
Bulk Cable Weight	16 lbs/1000 ft.
Max. Recommended Pulling Tension	27 lbs.
Min. Bend Radius (Install)	1.75 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
AWM Specification	UL Style 2092 (300 V 60°C)

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
---------------	----------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	88761, 87761, 82761

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	64 Ohms
Nom. Inductance	0.2 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	24 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	47 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	16 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS (UL AWM Style 2092)
Max. Recommended Current	2.9 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8761 0601000	2 #22 PE FS PVC	1000	18	CHROME	C
8761 06010000	2 #22 PE FS PVC	10000	170	CHROME	C Y
8761 0602000	2 #22 PE FS PVC	2000	36	CHROME	
8761 060500	2 #22 PE FS PVC	500	9	CHROME	



8761 Paired - Audio, Control and Instrumentation Cable

8761 0605000	2 #22 PE FS PVC	5000	90	CHROME	C
8761 060U1000	2 #22 PE FS PVC	U1000	17	CHROME	
8761 060U500	2 #22 PE FS PVC	U500	9	CHROME	

C = CRATE REEL PUT-UP.

Y = FINAL PUT-UP LENGTH MAY VARY -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

Revision Number: 1 Revision Date: 02-13-2004

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.