

## *Reconnector Module Pin-outs*

### **EXT MIC IN External balanced dynamic-mic connector**

Type: 3-pin Female XLR Audio Connector

Pin 1	Shield (circuit common)
Pin 2	Mic input +
Pin 3	Mic input -

### **EXT LINE IN Balanced Program Audio Input**

Type: 3-pin Female XLR Audio Connector

Pin 1	Shield (circuit common)
Pin 2	Mic input -
Pin 3	Mic input +

### **MIC PRE OUT Unswitched, Balanced Microphone Output**

Type: 3-pin Female XLR Audio Connector

Pin 1	Shield (circuit common)
Pin 2	Mic input +
Pin 3	Mic input -

### **HEADSET External Headset Connector**

Type: 9-Pin Male D-sub

Pin 1	External balanced dynamic mic input -
Pin 2	External balanced dynamic mic input shield (common)
Pin 3	Headset balanced dynamic mic input +
Pin 4	Headset balanced dynamic mic input -
Pin 5	Headphone +
Pin 6	External balanced dynamic mic input +
Pin 7	Electret panel mic audio input + and +5VDC bias
Pin 8	Electret panel mic common
Pin 9	Headphone -

### **SPKR External Speaker Output (8 ohms min, 2 watts max )**

Type: 3-Conductor, 1/4-inch phone jack

Tip	Speaker +
Ring	Speaker -
Sleeve	No Connection

This document was created with Win2PDF available at <http://www.win2pdf.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.  
This page will not be added after purchasing Win2PDF.