


REVIEWS			
REV	DESCRIPTION	DATE	CHANGED BY
A.	BETTERVIEW FROM MAC 9/10/2010. NEW FORMAT	10/24/09	D.ROSSELLO
B.	ECN 56-37 RE-DESIGN ALDIED LOGO REMOVED 2.5GTS AND WRITE IN	8/1/11	D.ROSSELLO



1. EACH OF THE THREE BRIDGING ABS SHELLS IN A PANEL ARE IDENTICAL, HAVING EIGHT RJ12 JACKS IN FRONT AND ONE 50 PIN MICRO-RIBBON (TELCO) (MALE OR FEMALE) CONNECTOR ON THE BACK.

2. EACH BRIDGING ASSEMBLY IS WIRED ACCORDING TO USOC (6 WIRE) REQUIREMENTS.

3. ALL CONNECTOR CONTACTS ARE GOLD PLATED.

1. STANDARDS 1.75" X 19.00" RACK PANEL DESIGN.

2. MATERIAL: (.06) 16 GAUGE SHEET STEEL.

3. FINISH: FLAT BLACK POWDER COAT.

4. MARKING: WHITE SILK-SCREENED NUMBERS AND LOGO.

5. ALL DIMENSIONS ARE REFERENCE ONLY.

JACK NO.	RJ12 PIN NO.	50 PIN CONNECTOR PIN NO.	JACK NO.	RJ12 PIN NO.	50 PIN CONNECTOR PIN NO.
1, 9 OR 17	4	26	5, 13 OR 21	4	38
	3	1		3	13
	2	27		2	39
	5	2		5	14
	1	28		1	40
	6	3		6	15
2, 10 OR 18	4	29	6, 14 OR 22	4	41
	3	4		3	16
	2	30		2	42
	5	5		5	17
	1	31		1	43
	6	6		6	18
3, 11 OR 19	4	32	7, 15 OR 23	4	44
	3	7		3	19
	2	33		2	45
	5	8		5	20
	1	34		1	46
	6	9		6	21
4, 12 OR 20	4	35	8, 16 OR 24	4	47
	3	10		3	22
	2	36		2	48
	5	11		5	23
	1	37		1	49
	6	12		6	24

NO CONNECTIONS TO TELCO CONTACTS 25 & 50

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES (mm)
OVERALL CABLE LENGTH TOLERANCE:
+1/2 [303] $\pm$ 1/25 [-0]
>1/2 [303] $\pm$ 60 [1524] $\pm$ 42 [107] / -0
>60 [1524] $\pm$ 120 [3048] $\pm$ 44 [1121] / -0
>120 [3048] $\pm$ 200 [7620] $\pm$ 66 [1521] / -0
>200 [7620] $\pm$ 3% / -0%

ALL OTHER DIMENSIONAL TOLERANCES:
X = $\pm$.2
Y = $\pm$.005
XXX = $\pm$.002

[illegible]

L-com® Global Connectivity
45 BEECHWOOD DRIVE
NORTH ANDOVER, MA
01845

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.