

Release Notes 2018/8

Ingest Scheduler Software PWA-ISC1 Version 1.0.2

[Overview]

PWA-ISC1 Ingest Scheduler Software is studio recording/transfer software for creating cutouts from material recorded on a PWS-4500 Multi Port AV Storage Unit, as required, and transferring them to external storage on a network drive.

In PWA-ISC1, a cutout/transfer task is referred to as a schedule. A schedule can be specified for a time slot of an existing recording or a future recording. A transfer for a time slot of an existing recording starts immediately. For a schedule specifying the time slot of a future recording, transfer starts when recording begins on the PWS-4500 at the specified time.

PWA-ISC1 V1.0 is able to install PWS-100MG1/PWS-110MG1, PWS-100PR1/PWS-110PR1.

[Version Information]

PWA-ISC1: V1.0.2 (V1.0.2.644)

Related products:

PWS-4500: V2.5

PWA-MGW1: V2.5

PWA-PRC1: V2.5

[Changes]

This version is released for combinations with PWS-4500 system version 2.5.

[Note]

- Only one PWA-ISC1 software should be connected to PRC Manager.
- System Frequency needs to be same within this system.
- Synchronizing the clocks on each device within this system. For details, see "Getting Started" in Installation Guide.
- When changing the items in [Real Time Clock Setup] on the [System] screen - the [Time] tab of the PWS-4500 Web menu, do [FS Format] on the [Storage] screen - [Setup] tab.
- Input an external reference TC to PWS-4500.
- Rebooting the PWA-ISC1 application software is required when PWS-4500 setting is changed.

- Media Gateway's spanning recording cannot be used. The item "Spanning REC" should be set OFF in [ISO REC Setting] on the Global menu [Settings] – [Server] page of Media Gateway.
 - File transfer fails when connected recording media was reconnected / Media Gateway was restarted. The connected recording media should remain connected during file transfer. When the file transfer failed, it will be necessary to set drive/folder for the scheduled recording clip(s) once again.
 - If proxy port is set within High-res port, it is necessary to create separate folders respectively when creating a schedule.
 - One Media Gateway is set as the transfer engine when setting more than one port at the same time in the schedule setting dialog. When using more than one Media Gateway, set a schedule for each Media Gateway.
-
- It cannot be used with the PWS-110CM1 Content Management Station.
 - HFR is not supported. (PWS-4500 should be recording at normal speed.)
 - BPU-4800 is not supported.